

ColorWorks® CW-C8000

High-Speed 4" Color Inkjet Label Printer



Fast, high-quality on-demand color label printing for high-volume runs.



Exceptional print quality — PrecisionCore® Heat-Free technology and UltraChrome® DL Inks deliver accurate colors, smooth gradations, precise barcodes and sharp text

High-speed, on-demand color labels — designed for mid- to high-volume batch runs, print multiple labels with variable data at speeds up to 12" per second¹

Reliable performance with PrecisionCore — built for demanding applications, permanent printhead means fewer interventions and low maintenance costs

High-yield 1.9 L total ink capacity² — ideal for high-volume batch runs, allowing for fewer interventions, low cost per milliliter and low consumable waste

ColorWorks' most advanced connectivity and remote management tools — integrate large fleets with Epson Cloud Solution PORT^{®3}, cloud printing and optional Wi-Fi[®]

Powerful fleet productivity with Epson Cloud Solution PORT³
— remotely view printer status, ink consumption and operation history

 $\label{eq:seamless workflow integration} Seamless workflow integration — compatible with ZPL II^{\$}, major middleware, SAP^{\$}, Windows^{\$}, Mac^{\$} and Linux^{\$}; built-in ESC/Label^{\$} language$

Durable, high-quality labels — UltraChrome DL Ink technology produces stunning labels that resist smudging, smearing and fading

High efficiency and low power consumption — PrecisionCore Heat-Free technology enables efficient ink usage and low energy usage

World-class service and support — includes a 1-year limited warranty; extended service plans available for up to a total of 5 years of continuous coverage

Designed for use exclusively with Epson ink packs*.





Printer

Print Method Line inkjet, dot matrix Print Resolution 600 dpi x 1200 dpi

Print Speed Up to 11.8" per second (300 mm/sec)

Color Adjustment Epson Preferred Color, Epson Standard, Epson Vivid Color

Media Dispense Type Auto cutter (scissor type), up to 1.5 million cuts

Printhead PrecisionCore printhead, permanent Paper-Feeding Mechanism Life 500 km

Ink Type UltraChrome DL SJIC47P pigment ink

Ink Colors Cyan, Magenta, Yellow and Black (Gloss or Matte

Ink Pack Configuration Four (4) individual ink packs, 480 mL each pack2

This printer is designed for use with genuine Epson packs only, not third-party packs or ink*.

Media

Supported Media Types Die-Cut Label, Full-Page Label, Continuous Label, Tag

Supported Media Constructions Plain Paper, Textured Paper, Matte Paper, Synthetic, Glossy Paper, Glossy Film, High Glossy Paper **Die-Cut Label Gap** 0.12" - 0.24" (3 mm - 6 mm)

Gap Sensor Position Adjustable; 0.12" – 2.20" (3 mm – 56 mm)

from left side; pitch: 0.04" (1 mm) Black Mark Sensor Position Fixed position; approximately

0.49" (12.4 mm) from left

Black Mark Width 0.75" (19 mm) or more from paper edge Black Mark Length 0.16" to 1.0" (4 mm – 25.4 mm) with 0.16" (4 mm) or more of white space around the black mark

Maximum Print Width 4.25" (108 mm)

Media Width

Internal Roll Media (Min. - Max.): 1.0" - 4.40" (25.4 mm - 112 mm)

External Roll Media, Fanfold (Min. - Max.): 1.97" - 4.40" (50 mm - 112 mm)

Media Length (Min. - Max.): 0.31" - 40"

(8 mm - 1,016 mm)Media Thickness (Min. - Max.): 3.30 mils - 23.62 mils

(0.084 mm - 0.600 mm)

Internal Roll Media Media Core Inner Diameter: 3.0" (76.2 mm) Media Maximum Outer Diameter: 8.0" (203.2 mm) Connectivity

USB USB 3.0 (one port), USB 2.0 (one port) Ethernet 1000Base-T/100Base-TX/10Base-T

Wi-Fi Optional Wi-Fi dongle available (OT-WL06) General-Purpose I/O Port D-Sub 25

Print Utilities and Remote Management Tools

EpsonNet SetupManager EpsonNet Config SE Epson Device Admin Epson Deployment Tool PrinterSetting

Color Tone Matching Assistant USB Printer Class Device Replacement

Enson Firmware Undater

Epson Cloud Solution PORT³ Production Monitor

General

Display 2.7" color LCD

Operating Systems Supported

Windows® 11

Windows 10 (32-bit/64-bit) Windows 8.1 (32-bit/64-bit)

Windows Server® 2022 Windows Server 2019 Windows Server 2016

Windows Server 2012 Windows Server 2012 R2

OS X® 10.9.5 or later, macOS® 10.12 or later CentOS® 7 (x86 64), Ubuntu 20.04 (x86 64)

Direct Command-Based Printing Zebra® ZPL II® native language support, plus command extensions, to allow for colorization of data; ESC/Label color command language; SAP® Direct Printing

Power Supply AC Direct

Temperature

Operating: 41 °F to 95 °F (5 °C to 35 °C), 20% to 80% RH Storage (When Ink Is Loaded and Charged): Gloss Black lnk: 5 °F – 104 °F (-15 °C – 40 °C), up to 120 H; Matte Black lnk: 14 °F – 104 °F (-10 °C – 40 °C),

Power Consumption Operating: 83.0 W

Standby: 3.3 W Power Off: 0.4 W

Rated Voltage 100 V - 240 V Rated Frequency 50 Hz - 60 Hz Acoustic Noise Approx. 57 dB EMI FCC Class A, ICES-003 Class A

Warranty 1-year limited warranty with Return for Repair

Weight and Dimensions

Printer Dimensions (W x D x H) 24.4" x 15.4" x 16.5" (620 mm x 392 mm x 420 mm)

Printer Weight 79.4 lb (35 kg)

Packaging Weight and Dimensions

Packaging Dimensions (W x D x H): 32.2" x 22.7" x 24.3" (818 mm x 576 mm x 616 mm) Packaging Weight 94.8 lb (43 kg)

Eco Features

RoHS compliant

End-of-life options available4

Epson America, Inc. is a SmartWay® Transport Partner⁵

What's Included

ColorWorks CW-C8000 printer (Gloss or Matte), four ink packs (CMYK), maintenance box, AC power adapter and cord, sample label roll and Start Here guide

Ordering Information

CW-C8000 Matte Printer	C31CL02A9981
CW-C8000 Gloss Printer	C31CL02A9991
SJIC47P-BK Gloss Black Ink Pack	C13T55N120
SJIC47P-MK Matte Black Ink Pack	C13T55N520
SJIC47P-C Cyan Ink Pack	C13T55N220
SJIC47P-M Magenta Ink Pack	C13T55N320
SJIC47P-Y Yellow Ink Pack	C13T55N420
SJMB7500 Maintenance Box for C7500, C8000	C33S020596
TU-RC8000 Take-Up Unit	C32C882501



Gateway Business Communications, Inc. 35 Philmack Drive Middletown, CT 06457 866-792-0031

www.gatebiz.com



